

# ESTABLISH-R™

14-0-5 ESTABLISHMENT ENHANCER

UTILIZING ELEMENTS OF 

## GUARANTEED ANALYSIS

Total Nitrogen (N).....14%

5% Urea Nitrogen

9% Controlled Release Nitrogen

Soluble Potash (K<sub>2</sub>O) .....5%

Molybdenum (Mo).....0.01%

Zinc (Zn).....0.2%

**DERIVED FROM: Urea, Urea-Triazone, Protein Hydrolysate, Potassium Acetate, Potassium Hydroxide, Sodium Molybdate, and Zinc EDTA**

## NON-PLANT FOOD INGREDIENTS

Humic acid .....5%

Fulvic acid .....10%

Seaweed extract .....20%

## GENERAL INFORMATION

**ESTABLISH-R™** is a unique combination of high-performance nutrients with soil and plant health enhancers that are designed and formulated to provide the highest impact on the establishment of crops, supporting root development and early plant performance. It is meant to complement a complete and balanced fertilization program and is not intended to fully provide all the nutrient requirements of any given crop.

## DIRECTIONS FOR USE

**SHAKE WELL BEFORE USE.** Use following established recommendations of a Certified Crop Advisor, Independent Crop Consultant, or Agricultural Extension Agent. Fill the spray tank halfway with water before adding **ESTABLISH-R™** to the mix. If mixing with other products, always do a compatibility jar test in small quantities to ensure proper mixing. **DO NOT MIX**

**WITH CALCIUM FERTILIZERS. DO NOT MIX WITH ACID FERTILIZER OR NUTRIENT SOLUTIONS WITH A pH BELOW 7.0.**

## RECOMMENDED RATES

**Soil Application Rate:** Apply 1-4 pints/acre to assist the establishment of crops like cotton, corn, wheat and small grains, soybeans, alfalfa, and vegetables in general. Agitate before use and dilute 1:20 with water before applying. Apply in -furrow with starter fertilizer or broadcast apply.

**Foliar Application Rate:** Apply 1-2 quarts/acre.

## PRECAUTIONARY STATEMENTS

Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye and face protection.

## STORAGE AND DISPOSAL

Store product locked up in original container in a dry and well-ventilated area. Do not store near heat or open flame. Do not contaminate water, food or feed by storage or disposal. Keep packaging closed, securely fastened and upright. Store product between 32° and 100°F (0° and 38°C). Avoid long-term storage at high temperatures. Do not store below 32°. Do not reuse product containers. Triple rinse (or equivalent) and add rinsate to spray tank. Offer rinsed container for recycling at an ARC site (go to [www.acrercycle.org](http://www.acrercycle.org) for locations) or by reconditioning or puncture and dispose of in a sanitary landfill or by other procedures approved by local, state, and federal regulations.



**DANGER**  
KEEP OUT OF REACH  
OF CHILDREN

## FIRST AID

**IF SWALLOWED:** Drink 8 – 16 ounces of water if conscious. Call a physician or poison control center immediately. Do not induce vomiting or give anything by mouth to an unconscious person.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present, and easy to do. Continue rinsing and call a poison control center or physician.

**IF ON SKIN:** Wash affected skin with soap and water. Remove contaminated clothing and launder clothing before reuse.

**IF INHALED:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and call a physician.

**FOR CHEMICAL EMERGENCY:** Call the **POISON CONTROL CENTER** at 800-222-1222

## CONDITIONS OF SALE AND LIMITATIONS OF WARRANTY AND LIABILITY

The manufacturer or seller makes no other expressed or implied warranty of fitness or merchantability of any other expressed or implied warranty. In no case shall the seller be liable for consequential, special, or indirect damage resulting from the use or handling of this product. The Manufacturer and the Seller offer this product, and the Buyer and User accept it, subject to the foregoing Conditions of Sale and Warranty, which may be varied only by agreement in writing signed by a duly authorized representative of the manufacturer.

## NET CONTENTS:

275 GALLON TOTE

## NET WEIGHT:

10.17 lbs/gallon

@ 68° F

MANUFACTURED FOR:



Carolina Eastern, Inc.  
347 McAllister Mill Road  
Scranton, SC 29591  
843-389-2761  
[CROPEXCELLENCE.COM](http://CROPEXCELLENCE.COM)

